

PRESSURE RELIEF VALVE

Background

[01] Pressure relief valves are typically used to selectively discharge pressurized fluid from a pressure vessel, piping system, or other equipment or sources of pressurized fluid. It is important for a pressure relief valve to reliably open at the set point of valve, i.e. the specified opening pressure of the valve, to avoid potentially dangerous overpressure conditions that can threaten the integrity of the pressure vessel. During normal operation of the pressure vessel, materials within the pressure vessel often collect on the exposed components of the valve, including, for example, the valve seat and the valve member of the valve. The build up of material can interfere with the operation of the valve by, for example, preventing the valve member of the valve from properly seating or causing the valve to open at a pressure higher than the set point of the valve.

Summary

[02] Pressure relief valves are disclosed herein that may be structured to minimize the build-up of material on the components of the valve and to facilitate the reliable and repeatable operation of the valve.

[03] In accordance with one exemplary embodiment, a pressure relief valve may include a housing having a passage formed therein for connection with a fluid source and a seal surface positioned about an opening in the passage. The housing may include a discharge opening for relieving pressurized fluid from the housing during operation of the relief valve. The pressure relief valve may also include a valve member positioned within the housing. The valve member may be movable along an axis within the cavity to selectively engage the seal surface in a sealing relationship. The housing may be sized and shaped to substantially restrict movement of the valve member to a direction parallel to the axis. The pressure relief valve may include a spring coupled to the valve member and a portion of the housing. The spring may apply a spring force to the valve member to bias the valve member into contact with the seal surface. In operation, the valve member may separate from the seal surface upon application of a fluid pressure force on the valve member that is greater than the spring force thereby allowing pressurized fluid to pass through the discharge opening in the housing.

[04] In certain exemplary embodiments, the valve member of the relief valve may have one or more through-holes formed therein. The one or more through-holes may be arranged on the valve member to inhibit fluid flow through the through-holes when the valve member is sealing engaged with the seal surface. The valve member may have a variety of sizes or shapes. In certain exemplary embodiments, the valve member may be disk-shaped having a generally circular bottom surface for engaging the seal surface. In embodiments in which the valve member is disk shaped, the through-holes may be arranged in a circular pattern about the circumference of the bottom surface.

[05] In certain exemplary embodiments, the valve member may include a spring recess sized to receive at least an end of the spring. The spring recess may be centered on the axis of motion of the valve member. The housing may include a second spring recess sized to receive another end of the spring, the second spring recess being aligned with the spring recess in the valve member.

[06] In certain exemplary embodiments, the housing may include a base and a housing cover engaging the base in a sealing relationship and enclosing the seal surface within a cavity formed in the cover. The fluid passage connecting with the fluid source may be formed in the base. The cavity within the cover may include the discharge opening for relieving pressurized fluid from the cavity during operation of the relief valve.

Brief Description of the Drawings

[07] These and other features and advantages of the devices and methods disclosed herein will be more fully understood by reference to the following detailed description in conjunction with the attached drawings in which like reference numerals refer to like elements through the different views. The drawings illustrate principles of the devices and methods disclosed herein and, although not to scale, show relative dimensions.

[08] FIGURE 1 is an exploded perspective view of an exemplary embodiment of a pressure relief valve;

[09] FIGURE 2A is side elevational view in cross-section of the pressure relief valve of FIGURE 1, illustrating the valve in the closed position;

[10] FIGURE 2B is side elevational view in cross-section of the pressure relief valve of FIGURE 1, illustrating the valve in the open position;

- [11] FIGURE 3A is a top view of the base of the pressure relief valve of FIGURE 1, illustrating the valve seat;
- [12] FIGURE 3B is a side elevational view in cross-section of the base of FIGURE 3A;
- [13] FIGURE 4A is bottom view of the valve member of the pressure relief valve of FIGURE 1;
- [14] FIGURE 4B is a side elevational view in cross-section of the valve member of FIGURE 4A;
- [15] FIGURE 5A is a top view of the housing cover of the pressure relief valve of FIGURE 1; and
- [16] FIGURE 5B is a side elevational view in cross-section of the housing cover of FIGURE 5A.

Detailed Description of Exemplary Embodiments

[17] To provide an overall understanding, certain exemplary embodiments will now be described; however, it will be understood by one of ordinary skill in the art that the devices and methods disclosed herein can be adapted and modified to provide devices and methods for other suitable applications and that other additions and modifications can be made without departing from the scope of the disclosure.

[18] Unless otherwise specified, the illustrated embodiments can be understood as providing exemplary features of varying detail of certain embodiments, and therefore features, components, and/or aspects of the illustrations can be otherwise combined, separated, interchanged, and/or rearranged without departing from the present disclosure.

[19] An exemplary embodiment of a pressure relief valve 10 is illustrated in FIGURE 1. In the exemplary embodiment of FIGURE 1, the valve 10 includes a housing 12 that may comprises a base 14 and a housing cover 16. The exemplary valve 10 also includes a valve member 18 that is positioned with the housing cover 16 and operates to selectively engage a seal surface 20 on the base 14 in a sealing relationship. The exemplary pressure relief valve 10 may be attached to a pressure vessel or other potential source of pressurized fluid to relive fluid pressure from the pressure vessel in overpressure conditions.

[20] In the exemplary embodiment, the base 14 includes a passage 22 formed through the base 14 for connecting the valve 10 with a fluid source, e.g., a pressure vessel or piping. The base 14, as illustrated in FIGURES 3A and 3B, may be generally mushroom shaped with the passage 22

extending from a bottom surface 24 to a top surface 26 of the base 14. The bottom surface 24 may be an annular flange positioned about an end of the passage 22, as shown in FIGURE 3B, or may be any other structure that facilitates the connection of the valve 10 to a source of pressurized fluid. The top surface 26 may include the seal surface 20 that is positioned about an opening 28 at an end of the passage 22. The seal surface 20 forms a valve seat for the valve member 18 to selectively engage in a sealing relationship. The seal surface 20 in the exemplary embodiment is generally annular in shape, although, other shapes are possible, including, for example, elliptical and rectilinear shapes. Referring to FIGURES 1, 3A and 3B, the seal surface 20 in the exemplary embodiment includes an annular groove 30 that is sized and shaped to receive an optional elastomeric seal ring 32, e.g. a rubber O-ring, within the groove 30.

[21] The top surface 26 may also include a secondary seal surface 34 for engaging the housing cover 16 in a sealing relationship. The secondary seal surface 34 is preferably located radially outside of the seal surface 20 and may be shaped in a manner analogous to the seal surface 20. The secondary seal surface 34 in the exemplary embodiment includes an annular groove 36 that is sized and shaped to receive an optional elastomeric seal ring 38, e.g. a rubber O-ring, within the groove 36. One or more bolt holes 40 may also be formed through the secondary seal surface 34 to receive housing bolts 42. Housing bolts 42 may be provided to secure the base 14 to the housing cover 16.

[22] The valve member 18 in the exemplary embodiment may be disk-shaped having a generally circular bottom surface 44 spaced apart from a generally circular top surface 46 that is oriented parallel to the bottom surface 44, as illustrated in FIGURES 1, 4A, and 4B. When the pressure relief valve 10 is closed, the bottom surface 44 of the valve member 18 engages the seal surface 20 to inhibit the flow of fluid through the opening 28 in fluid passage 22. FIGURE 2A illustrates the valve member 18 in the closed position, i.e. in sealing contact with the seal surface 20. In the exemplary embodiment, the valve member 18 has one or more through-holes 48 formed through the valve member 18. The through-holes 48 may be provided to permit fluid to flow through the valve member 18 when the pressure relief valve 10 is open, i.e., when the bottom surface 44 of the valve member 18 is separated from the seal surface 20. FIGURE 2B illustrates the valve member 18 in an open position.

[23] In the exemplary embodiment, the through-holes 48 may be arranged in a circular pattern, illustrated by line H in FIGURE 4A, about the circumference of the valve member 18.

Preferably, the through-holes 48 are uniform in size and shape and are symmetrically disposed about the circumference of the valve member 18. The through-holes 48 may also be evenly spaced apart. A symmetrical arrangement of commonly structured and spaced through-holes 48 may cause fluid to evenly dissipate through the valve member 18. This arrangement facilitates the valve member 18 maintaining a proper alignment within the housing cover 16 as the valve member moves from a closed position to an open position. One skilled in the art will appreciate, however, that the number, arrangement, and spacing of the through-holes 48 may be varied depending, for example, on the desired volume of fluid pressure to be relieved by the valve 10 and the size of the opening 28 in the passage 22. The through-holes 48 may be arranged on the valve member 18 to inhibit fluid flow through the through-holes 48 when the valve member 18 is in the closed position. For example, the diameter of the circular pattern H may be greater than the diameter of the opening 28 in the fluid passage 22. In embodiments including an elastomeric seal ring 32, the diameter of the circular pattern H may be greater than the diameter of the annular groove 30.

[24] The pressure relief valve 10 may also include a spring 50, illustrated in FIGURE 1, that may be coupled to the valve member 18 and a portion of the housing 12. The spring 50 applies a spring force to the valve member 18 to bias the valve member 18 into contact with the seal surface 20. The spring 50 maintains the valve member 18 in a closed position during normal operating conditions. In an over pressure condition, fluid pressure on the bottom surface 44 of the valve member 18 may overcome the spring force on the top surface 46 of the valve member 18, causing the valve 10 to open by separation of the valve member 18 from the seal surface 20. When the valve 10 is open, pressurized fluid may pass through the through-holes 48 in the valve member 18 and/or around the valve member 18 and out a discharge opening 60 in the cover 16 of the housing 12. The opening pressure of the valve 10 may be set by selecting a spring 50 having a corresponding spring force.

[25] Continuing to refer to FIGURES 4A and 4B, the valve member 18 may also include an optional spring recess 52 sized to receive at least an end of the spring 50. The spring recess 52, when present, serves to facilitate the alignment of the spring 50 during operation of the valve 10. The spring recess 52 may have a cross-sectional shape that is analogous to the cross-sectional shape of the spring 50. For example, in the case of a spring 50 having a circular cross-section, as illustrated in FIGURE 1, the spring recess 52 also may have a circular cross-section, as

[29] The valve member 18 may be movable in a reciprocating manner along an axis of motion A, illustrated in FIGURE 2A and 2B, within the cavity 60 to selectively engage the seal surface 20 of the base 14 in a sealing relationship. In certain exemplary embodiments, the axis of motion A of the valve member 18 may be a center-line C_h, illustrated in FIGURES 5A and 5B, of the housing cover 14 and the cavity 60. The valve member 18 may be positioned in the cavity 60 such that the center-line C_h of the housing cover 16 is coaxial with the center-line C_v, of the valve member 18, illustrated in FIGURES 4A and 4B. The center-line C_h of the housing cover 16 may also be coaxially aligned with the center-line C_b, of the base 14, illustrated in FIGURES 3A and 3B. Thus, in certain exemplary embodiments, the center-line C_h of the housing cover 16, the center-line C_v, of the valve member 18, and the center-line C_b, of the base 14 may be

coaxially aligned and the axis of motion A of the valve member 18 may be along the coaxial center-line of the housing cover 16, the valve member 18, and the base 14. FIGURES 2A and 2B illustrate an exemplary embodiment of the valve 10 in which the center-lines of the housing cover 16, the member 18, and the base 14 are coaxially aligned.

[30] The cavity 60 of the housing cover 16 may be sized and shaped to substantially restrict movement of the valve member 18 to a direction parallel to the axis of motion A of the valve member 18, as illustrated in FIGURES 2A and 2B. In the exemplary embodiment illustrated in FIGURES 2A and 2B, the housing cavity 60 has a cross-sectional shape analogous to the cross-sectional shape of the valve member 18 and the clearance between the valve member 18 and the walls of the cavity 60 is minimized, such that the diameter of the cavity 60 is approximate to the diameter of valve member 18. In certain exemplary embodiments, the clearance between the valve member 18 and the walls of the cavity 60 is less or equal to 0.10 inches. In other exemplary embodiments, the clearance is less than or equal to approximately 0.02 inches.

[31] The housing cover 16 may include a second spring recess 64 sized to receive another end of the spring 50. The second spring recess 64 may be aligned with the spring recess 52 in the valve member 18. In the exemplary embodiment illustrated in FIGURES 2A and 2B, the spring recess 52 and the second spring recess 64 are coaxially aligned on the coaxial centerline of the housing cover 16, the valve member 18, and the base 14.

[32] The components of the exemplary valve 10, such as the housing cover 16, the base 14, and the valve member 18, may be constructed from metals, including for, example, stainless steel or aluminum, plastics, or other materials suitable for constructing fluid handling components. The particular material of the pressure relief valve may be selected based on the environment in which the valve is intended to operate and the fluid(s) to which the valve 10 may be exposed.

[33] In operation, the spring 50 of the exemplary valve 10 illustrated in FIGURES 2A and 2B biases the valve member 18 into a closed position in which the valve member 18 is in contact with the seal surface 20. In the closed position illustrated in FIGURE 2A, fluid may not flow through or by the valve member 18 from the fluid passage 22. The through-holes 48 in the valve member 18 of the exemplary valve 10 are radially distal from the opening 28 in the fluid passage 22 and may be further isolated from the fluid within the fluid passage 22 by the optional elastomeric seal ring 32. This arrangement of the through-holes 48 may inhibit the build-up of materials from the fluid on the through-holes 48 and/or the edges of the valve member 18. In an

111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532
 533
 534
 535
 536
 537
 538
 539
 540
 541
 542
 543
 544
 545
 546
 547
 548
 549
 550
 551
 552
 553
 554
 555
 556
 557
 558
 559
 560
 561
 562
 563
 564
 565
 566
 567
 568
 569
 570
 571
 572
 573
 574
 575
 576
 577
 578
 579
 580
 581
 582
 583
 584
 585
 586
 587
 588
 589
 590
 591
 592
 593
 594
 595
 596
 597
 598
 599
 600
 601
 602
 603
 604
 605
 606
 607
 608
 609
 610
 611
 612
 613
 614
 615
 616
 617
 618
 619
 620
 621
 622

[35] It is also to be understood that the following claims are to cover all generic and specific features of the devices and methods described herein.